



## Products & Features Matrix

	Key: Sensor: I = Internal E = External* Battery: F = Fixed R = Replaceable Alarm Settings: P = Preset C = Configurable	Main Features			Usage		Memory			Connectivity			Other Features				
		Temperature Measurement Range	Sensor	Battery	Multi-Use	Single-Use	~4,000 Logs Memory	~8,000 Logs Memory	~16,000 Logs Memory	Cradle Required	USB Connector	Wifi Connectivity	Auto PDF Output	Display	Audible Alarm	Alarm Settings	WHO PQS Listed
<b>Temperature Data Loggers</b>		<b>Product Model</b>															
Temperature Logger	TRIX-8	-40° to +85° C	I	F	✓			✓		✓					C	✓	
High Memory Temperature Logger	TRIX-16	-40° to +85° C	I	F	✓				✓					C			
Temperature Logger with External Probe*	TREX-8	-40° to +99° C	E	F	✓				✓					C			
Single-Use Temperature Logger	SRIC-4	-30° to +60° C	I	F		✓	✓			✓				C			
Logger with 30 day display + Fixed Battery	TRID30-7F	-30° to +60° C	I	F	✓			✓		✓			✓	C			
Logger with 30 day display + Replaceable Battery	TRID30-7R	-30° to +60° C	I	R	✓			✓		✓			✓	C			
WHO PQS listed Logger for vaccines	VaxTag	-30° to +60° C	I	F	✓			✓		✓			✓	P		✓	
Logger with 30 day display + External Probe*	TRED30-16R	-40° to +99° C	E	R	✓			✓		✓			✓	✓	C		
<b>USB Temperature Data Loggers</b>																	
Temperature Logger	USRIC-4	-30° to +60° C	I	F		✓	✓			✓				C			
PDF Logger	USRIC-8	-30° to +60° C	I	F		✓		✓		✓		✓		C			
PDF High Memory Logger	UTRIX-16	-30° to +70° C	I	F	✓				✓	✓		✓		C			
PDF Logger with display + Fixed Battery	UTRID-16	-30° to +60° C	I	F	✓				✓	✓		✓	✓	C		✓	
PDF Logger with display + Replaceable Battery	UTRID-16R	-30° to +60° C	I	R	✓				✓	✓		✓	✓	C			
PDF Logger with display & External Probe*	UTRED-16F	-40° to +99° C	E	F	✓				✓	✓		✓	✓	C			
PDF Single-Use Logger with display	USRID-16	-30° to +60° C	I	F		✓			✓	✓		✓	✓	C			
WHO PQS Listed PDF Logger with display	USRID-16W (1 / 2)	-30° to +60° C	I	F		✓			✓	✓		✓	✓	P		✓	
Logger with Large display & External Probe*	UTRED30-16	-40° to +99° C	E	R	✓				✓	✓		✓	✓	✓	C		
<b>Wifi Temperature Data Loggers</b>																	
WiFi logger with large display & External Probe*	UTRED30-WIFI	-40° to +99° C	E	R	✓			✓		✓	✓	✓	✓	✓	C		
Low Temp WiFi logger with large display & Ext. Probe*	UTREL30-WIFI	-90° to +40° C	E	R	✓			✓		✓	✓	✓	✓	✓	C		

\* Extra Charges Apply For Probes & Accessories

# LogTag<sup>®</sup>

## Products & Features Matrix

		Key:			Main Features		Usage		Memory			Connectivity			Other Features												
		Sensor: I = Internal E = External*			Battery: F = Fixed R = Replaceable			Alarm Settings: P = Preset C = Configurable		Temperature Measurement Range	Sensor	Battery	Multi-Use	Single-Use	~4,000 Logs Memory	~8,000 Logs Memory	~16,000 Logs Memory	Cradle Required	USB Connector	Wifi Connectivity	Auto PDF Output	Display	Audible Alarm	Alarm Settings	WHO PQS Listed		
<b>Low-Temperature Data Loggers</b>		<b>Product Model</b>																									
Low Temp Logger	TRIL-8	-80° to +40° C	I	F	✓			✓					✓			✓											C
Single-Use Logger	SRIL-8	-80° to +40° C	I	F		✓							✓			✓											C
Logger with External Probe*	TREL-8	-90° to +40° C	E	F	✓								✓			✓											C
USB PDF Logger with External Probe*	UTREL-16F	-90° to +40° C	E	F	✓									✓			✓			✓	✓						C
Logger with 30 day display & External Probe*	TREL30-16	-90° to +40° C	E	R	✓									✓			✓				✓	✓					C
USB Logger with large display & External Probe*	UTREL30-16	-90° to +40° C	E	R	✓										✓		✓			✓	✓	✓					C
<b>Temperature and Humidity Data Loggers</b>																											
Humidity & Temperature Logger	HAXO-8	-40° to +85° C	I	F	✓								✓			✓											C
Single-Use Humidity & Temperature Logger	HASO-8	-40° to +85° C	I	F		✓							✓			✓											C
USB PDF Humidity/Temperature Logger with display	UHADO-16	-30° to +70° C	I	R	✓									✓			✓			✓	✓	✓					C
<b>Temperature Indicators</b>																											
Temperature Indicator with 20 day display	TIC20	-30° to +60° C	I	F		✓															✓					P	✓
Temperature Indicator with 4 alarms	TICT	-25° to +60° C	I	F		✓															✓					P	
Freeze Temperature Indicator	TICT iS0*Tag®	-25° to +60° C	I	F		✓															✓					P	✓
<b>Interface Cradles</b>																											
Desktop USB Interface Cradle	LTI-HID	-20° to +60° C	N/A	N/A	✓												✓										N/A
LTI WiFi Interface Cradle	LTI-WIFI	0° to +40° C	N/A	N/A	✓												✓	✓									N/A
LTI Wall Mount WiFi Interface Cradle	LTI-WM-WIFI	-25° to +40° C	N/A	N/A	✓												✓	✓									N/A

\* Extra Charges Apply For Probes & Accessories

LogTag dataloggers are named using the naming conventions below. Please note that these features may not be accurate, so please to check the product specifications before purchase.

- T** Temperature
- R** Recording
- I** Internal Sensor
- X** Extended Temp Range
- S** Single Use
- C** Commercial Temp Range (-30°C to +60°C)
- D** Display
- U** USB
- E** External Sensor
- L** Low Temperature

- H** Humidity
- F** Fixed Battery
- R** Replaceable Battery
- W** WHO-PQS Listed
- 4** ~4,000 Log Memory
- 7** ~7,000 Log Memory
- 8** ~8,000 Log Memory
- 16** ~16,000 Log Memory
- 20** 20-Day Display
- 30** 30-Day Display
- WIFI** WiFi Enabled