




Product Name	<u>TRIX-8</u>	<u>HAXO-16BT</u>	<u>LT5GEO</u>
Core Benefit	Affordable Large Scale Mapping	At-a-glance Humidity Monitoring	Automated Uploads and Reporting
Customer Needs	<ul style="list-style-type: none"> • Popular logger • Easy configuration • Robust Logger • Fast data downloads • WHO PQS listed 	<ul style="list-style-type: none"> • Dew point monitoring • Easy configuration • Slim design • Easy to redeploy and restart without removing the logger 	<ul style="list-style-type: none"> • No need to involve IT • Automatic data upload to LogTag® Online • Humidity monitoring • Real-time measurement updates
Temperature Measurement Range	-40 °C to +85 °C -40 °F to +185 °F	-20 °C to +70 °C -4 °F to +158 °F	-30 °C to +70 °C -22 °F to +158 °F
On Device Memory	8,000 readings 53 days with 10 minute sampling	16,000 paired readings 169 days with 15 minute sampling	16,000 paired readings 112 days with 10 minute sampling
Battery Life and Type	3 years Fixed	1 year Fixed	112 days Rechargeable
Alarm Notifications	Visual	Visual	Visual Audible Instant VoiceCall, SMS, WhatsApp alerts
Automatic Reports Via LogTag® Online		✓	✓
Data Available during Mapping		✓	✓
Humidity Sensor		✓	✓
LTI HID Cradle Compatible	✓		
Compliance	 EN 12830	-	-
Price	\$	\$ \$	\$ \$ \$

*Loggers compatible with additional probes

LogTag® Analyzer 3

Powerful Multi-graphing

Easy visualization by allowing data from multiple loggers to be seen on single graph.



Rugged Case

Strong polycarbonate casing designed to withstand tough conditions



21 CFR Part 11 Compliance

LogTag® solutions comply with 21 CFR Part 11's strict standards