



Product Name	<a href="#">TRIX-8</a>	<a href="#">UTRID-16R</a>	<a href="#">LT5GEO-M</a>
Core Benefit	<b>Reliable and Fast</b>	<b>Displayed Convenience</b>	<b>Cellular Automation</b>
Customer Needs	<ul style="list-style-type: none"> <li>• Popular logger</li> <li>• Easy configuration</li> <li>• Slim design, small footprint in package</li> <li>• Long battery life</li> </ul>	<ul style="list-style-type: none"> <li>• Software-free downloads</li> <li>• At-a-glance monitoring</li> <li>• Easy review of key statistics on device</li> </ul>	<ul style="list-style-type: none"> <li>• Automatic data upload to cloud storage</li> <li>• Automatic flight mode</li> <li>• Real-time alarms</li> <li>• Shipment location tracking</li> </ul>
Temperature Measurement Range	-40 °C to +85 °C -40 °F to +185 °F	-30 °C to +60 °C -22 °F to +140 °F	-30 °C to +70 °C -22 °F to +158 °F
On Device Memory	8,000 readings 53 days with 10 minute sampling	16,000 readings 56 days with 5 minute sampling	16,300 readings 112 days with 10 minute sampling
Battery Life and Type	3 Years Fixed	1 Year Replaceable	112 days Rechargeable
Connectivity	LTI-HID Interface	USB-A	Cellular USB-C
Other Sensors			Humidity Light Shock GPS Location
VoiceCall, SMS, WhatsApp Alerts			✓
USB PDF Reports		✓	✓
IATA Non-Dangerous	✓	✓	✓
Price	\$	\$\$	\$\$\$
Single Use Model Code	<a href="#">SRIC-4</a>	<a href="#">USRID-16</a>	<a href="#">LT5GEO-S</a>
External Probe Model Code	<a href="#">TRES-8</a>	<a href="#">UTRED-16F</a>	<a href="#">LT5GEO-E-M</a>



### Multi-Trip

Get more value and reuse a single logger for multiple shipments

### LogTag® Online

#### LogTag® Online - Cloud

Securely store over 1 million recordings and enable easy sharing with relevant staff



21 CFR Part 11

### Compliance

LogTag® solutions comply with 21 CFR Part 11's strict standards