



Product Name	<u>TRIL-16U</u>	<u>UTREL-16F</u>	<u>TREL30-16</u>
Core Benefit	Wireless Simplicity	Easy Downloads With Display	Comprehensive on Screen Review
Customer Needs	<ul style="list-style-type: none"> • Software free downloads • Internal probe • Wire-free shipment monitoring • Single-use option 	<ul style="list-style-type: none"> • Software free downloads • Alarms on display • Review stats without opening the shipment 	<ul style="list-style-type: none"> • At-a-glance monitoring • 30 days of alarms on the display • Review stats without opening the shipment
Temperature Measurement Range	-85 °C to +40 °C -121 °F to +104 °F	-90 °C to +40 °C -130 °F to +104 °F	-90 °C to +40 °C -130 °F to +104 °F
On Device Memory	16,000 readings 66 days at 6 minute sampling	16,000 readings 112 days at 10 minute sampling	15,900 readings 66 days at 6 minute sampling
Battery Type and Life	1,000 hours at -85 °C Fixed	2 Years Fixed	1 Year Replaceable
30 Days of Alarms on Display			✓
Audible Alarms			✓
Min/Max on Display		✓	✓
CDC/VFC Compliant		✓	✓
USB PDF Reports	✓	✓	
Internal Probe	✓		
Recommended Probe*	N/A	<u>ST10M</u>	<u>ST10M</u>
Price	\$	\$\$**	\$\$\$**

*Loggers compatible with additional probes

**Includes the recommended probe price



Multi-Trip

Get more value and reuse a single logger for multiple shipments



Dry Ice Temperatures

Wide temperature range including dry ice temperatures to monitor your most vulnerable shipments



21 CFR Part 11

Compliance

LogTag® solutions comply with 21 CFR Part 11's strict standards