



Product Name	<u>HAXO-8</u>	<u>UHADO-16</u>	<u>LT5GEO-M</u>
Core Benefit	Easy Humidity Monitoring	Comprehensive on Screen Review	Cellular Automation
Customer Needs	<ul style="list-style-type: none"> • Long Battery Life • Easy configuration • Slim design • High Visibility alarms 	<ul style="list-style-type: none"> • Easy data download • At-a-glance monitoring • Noticeable audible alarms to alert staff 	<ul style="list-style-type: none"> • Real-time instant alerts to key personnel • External power charging • Auto Data upload to cloud
Temperature Measurement Range	-40 °C to +85 °C -40 °F to +185 °F	-30 °C to +70 °C -22 °F to +158 °F	-30 °C to +70 °C -22 °F to +158 °F
On Device Memory	8,000 readings 35 days at 10 minute sampling	16,000 readings 112 days at 10 minute sampling	16,300 readings 112 days with 10 minute sampling
Alarm Notifications	Visual	Visual Audible	Visual Audible Instant VoiceCall, SMS, WhatsApp alerts
Connection type	LTI-HID	Micro USB LTI-HID	Cellular USB-C
Battery Life and Type	3 Year Fixed	1 Year Replaceable	112 days Rechargeable
Min/Max at a Glance		✓	✓
Software Free Operation		✓	✓
USB PDF Report		✓	✓
Multi-Use	✓	✓	✓
Price	\$	\$ \$	\$ \$ \$



Dew Point Monitoring

Record paired temperature and humidity reading to easily see if the dew point was reached

LogTag® Online

LogTag® Online - Cloud

Securely store over 1 million recordings and enable easy sharing with relevant staff



21 CFR Part 11

Compliance

LogTag® solutions comply with 21 CFR Part 11's strict standards