



Product Name	<u>USRIC-16</u>	<u>HASO-8</u>	<u>SRIL-16U</u>
Core Benefit	Easy Operation	Simple Humidity Monitoring	Dry Ice Monitoring
Customer Needs	<ul style="list-style-type: none"> Automatic Generation of PDF/CSV report Affordable efficient choice Instruction easy to follow with 2 buttons 	<ul style="list-style-type: none"> Two different monitoring in one Visual alerts reduces chance of failing Single button start 	<ul style="list-style-type: none"> No action needed during dry ice shipment Easy download simplifies supply chain integration
Temperature Measurement Range	-30 °C to +60 °C -22 °F to +140 °F	-40 °C to +85 °C -40 °F to +185 °F	-85 °C to +40 °C -121 °F to +104 °F
On Device Memory	16,129 readings 56 days at 5 minute sampling	8,003 pairs readings 53 days at 10 minute sampling	16,000 readings 66 days at 6 minute sampling
IP Rating	IP64	IP61	IP65
Connection type	USB-A	LTI-HID	USB-A
Battery Life	6 months	6 months	1,000 hours at -85 °C
Humidity Sensor		✓	
USB PDF Report	✓		✓
Software Free Operation	✓		✓
Alarm Notifications	✓	✓	✓
Pre-start Feature	✓	✓	✓
Price	\$	\$ \$	\$ \$ \$



Fail Safety Reporting

Reduce human error by capturing data even when the start button is forgotten



LogTag® Online - Cloud

Securely store over 1 million recordings and enable easy sharing with relevant staff



21 CFR Part 11

Compliance

LogTag® solutions comply with 21 CFR Part 11's strict standards