



Product Name	UTRID-16R	UHADO-16	UTRED30-WIFI
Core Benefit	Simple Monitoring with Display	Comprehensive on Screen Review	Streamlined Automation
Customer Needs	<ul style="list-style-type: none"> At-a-glance monitoring Easy review of key statistics on device 	<ul style="list-style-type: none"> Large display Dew point monitoring Easy data download 	<ul style="list-style-type: none"> Automated monitoring Two locations, one logger Easy calibration
Temperature Measurement Range	-30 °C to +60 °C -22 °F to +140 °F	-30 °C to +70 °C -22 °F to +158 °F	-40 °C to +99 °C -40 °F to +210 °F
On Device Memory	16,000 readings 56 days at 5 minute sampling	16,000 readings 112 days at 10 minute sampling	16,000 readings 67 days at 6 minute sampling
Alarm Notifications	Visual	Visual Audible	Visual Audible Instant VoiceCall, SMS, WhatsApp alerts
Connection type	USB-A	Micro USB Varo LTI-HID	Micro USB Varo app WiFi
Battery Life and Type	1 Year Replaceable	1 Year Replaceable	2 months back up External power
Automatic Data Upload to Cloud			✓
Dual Channel			✓
Internal Probe	✓	✓	
Software Free Operation	✓	✓	
Recommended Probe*	-	-	CP100K Smart Probe
Price	\$	\$ \$	\$ \$ \$

*Loggers compatible with additional probes



USB Reporting

Easily download CSV and PDF reports software-free with built-in USB connections



Min and Max On Display

Easily review critical data with minimum and maximum values on screen for at a glance review



21 CFR Part 11

Compliance

LogTag® solutions comply with 21 CFR Part 11's strict standards