





Product Name	<u>UTRID-16R</u>	<u>HAXO-16BT</u>	<u>TRED30-16U</u>	<u>LT5GEO-M</u>
Core Benefit	Affordable Monitoring	Easy Operation and Tracking	Comprehensive on Screen Review	Cellular Automation
Customer Needs	<ul style="list-style-type: none"> • Software-free downloads • Slim design, small footprint in package • Simple configuration 	<ul style="list-style-type: none"> • Easier wireless download • Dew point monitoring • Slim Design • Monitoring from a distance 	<ul style="list-style-type: none"> • At-a-glance monitor display • Easy software free data downloads • Noticeable audible alarm 	<ul style="list-style-type: none"> • Automatic data upload to cloud storage • Automatic flight mode • Real-time alarms • Shipment location
Temperature Measurement Range	-30 °C to +60 °C -22 °F to +140 °F	-20 °C to +70 °C -4 °F to +158 °F	-40 °C to +99 °C -40 °F to +210 °F	-30 °C to +70 °C -22 °F to +158 °F
On Device Memory	16,000 readings 56 days at 5 minute sampling	16,000 paired readings 169 days 15 min sampling	17,526 readings 60 days at 5 minute sampling	16,000 readings 112 days at 10 minute sampling
Alarm Notifications	Visual	Visual	Visual Audible	Visual Audible Instant VoiceCall, SMS, WhatsApp alerts
Connection type	USB-A	Bluetooth	USB-C LTI-HID	Cellular USB-C
Battery Life and Type	1 year Replaceable	1 year Fixed	1 year Replaceable	112 days Rechargeable
Humidity		✓		✓
Min/Max on Display	✓	✓	✓	
Compliance	EN 12830	-		
Recommended Probe	-	-	<u>ST100K</u>	-
Price	\$	\$ \$	\$ \$ \$	\$ \$ \$ \$



Easy Reporting

Easily download CSV and PDF reports direct from the logger or App.

LogTag® Online

LogTag® Online - Cloud

Easy to share and securely store over 1 million recordings and enable easy sharing with relevant staff



21 CFR Part 11

Compliance

LogTag® solutions comply with 21 CFR Part 11's strict standards