



Product Name	<u>UTRED-16F</u>	<u>TRED30-16U</u>	<u>UTRED30-WiFi</u>
Core Benefit	Affordable Convenience	Enhanced Connectivity	Streamlined Automation
Customer Needs	<ul style="list-style-type: none"> • Over 100 days of continuous monitoring • Software free operation • Affordable monitoring 	<ul style="list-style-type: none"> • At-a-glance monitoring • Long usable life • Easy calibration • Software free downloads 	<ul style="list-style-type: none"> • Real-time visibility through online portal • Monitor 2 environments with a single data logger • Easy calibration
On-Device Memory	16,100 readings 112 days with 10 minute sampling	17,500 readings 60 days with 5 minute sampling	32,000 (16,000 per probe) 67 days with 6 minute sampling
Cloud Storage	Over 1 million recordings	Over 1 million recordings	Over 1 million recordings
Battery Life	2 Years	1 Year	External Power 2 Months Back-Up
Software Free Data Downloads	✓	✓	
User Replaceable Battery		✓	✓
30 Day on Display Alarm Review		✓	✓
Audible Alerts		✓	✓
Real-Time Online Data Upload			✓
VoiceCall, SMS, WhatsApp Alerts			✓
Dual Environment Monitoring			✓
Connectivity	USB-A	LTI-HID Cradle or USB-C	Wi-Fi or Micro USB
Recommended Probe*	<u>ST100K</u>	<u>CP100 Smart Probe</u>	<u>CP100 Smart Probe</u>
Price	\$	\$ \$	\$ \$ \$

*Loggers compatible with additional probes



Min and Max On Display
Easily review critical data with minimum and maximum values on screen for at a glance review



Wide Temperature Range
Measure temperatures between -40 °C and +99 °C, suitable for most applications



Compliance

