



| Product Name | <u>UTRED-16F</u> | <u>TRED30-16</u> | <u>TRED30-16U</u> |
|---------------------------------------|---|--|--|
| Core Benefit | Affordable Convenience | At-a-Glance Review, Easy Calibration | Flexible and Software Free |
| Customer Needs | <ul style="list-style-type: none"> • Software free PDF and CSV report downloads • Long battery life • Cost effective multi-trip monitoring | <ul style="list-style-type: none"> • Easy calibration • Fast report downloads • At-a-glance 30 day alarm review | <ul style="list-style-type: none"> • Easy calibration • USB-C connectivity • Ready to use, no configuration • Simplified display |
| Memory Capacity | 16,100 readings 112 days with 10 minute sampling | 15,900 readings 66 days with 6 minute sampling | 17,500 readings 60 days with 5 minute sampling |
| Connection | USB-A | LTI-HID Interface Cradle | USB-C or LTI-HID Interface Cradle |
| Battery Life | 2 Years | 1 Year | 1 Year |
| Software Free Reports | ✓ | | ✓ |
| Min and Max on Display | ✓ | ✓ | ✓ |
| 30 Day on Display Alarm Review | | ✓ | ✓ |
| Smart Probe Compatible | | ✓ | ✓ |
| User Replaceable Battery | | ✓ | ✓ |
| Audible Alarms | | ✓ | ✓ |
| LogTag® Online Compatible | ✓ | ✓ | ✓ |
| Recommended Probe* | <u>ST100K</u> | <u>CP110 Smart Probe</u> | <u>CP100 Smart Probe</u> |
| Price | \$ | \$\$ | \$\$\$ |

*Loggers compatible with additional probes

LogTag® Online

LogTag® Online

Securely store over 1 million recordings and enable easy sharing with relevant staff



Wide Temperature Range

Measure temperatures between -40 °C and +99 °C, suitable for most applications



Compliance



21 CFR Part 11