



Product Name	<a href="#">TREL30-16CP</a>	<a href="#">UTREL30-16</a>	<a href="#">UTREL30-WiFi</a>
Core Benefit	<b>Affordable Monitoring</b>	<b>Dual Monitoring Instant Review</b>	<b>Streamlined Automation</b>
Customer Needs	<ul style="list-style-type: none"> <li>At-a-glance alarm review on screen</li> <li>Visual and audible alarms</li> <li>Simple calibration</li> </ul>	<ul style="list-style-type: none"> <li>Quick stats, no interaction needed</li> <li>Dual location monitoring</li> <li>Software-free reports</li> <li>Easy calibration</li> </ul>	<ul style="list-style-type: none"> <li>Dual location monitoring</li> <li>Automatic data uploads to LogTag® Online</li> <li>Instant alarm alerts</li> <li>Key stats on large display</li> </ul>
On Device Memory	15,900 readings 66 days at 6 minute sampling	16,000 readings per probe 67 days at 6 minute sampling	16,000 readings per probe 67 days at 6 minute sampling
Power Source	3V CR2032 with 1 year life	External Power AAA with 1 year life	External Power AAA 2 month life back up
Alarm Notifications	Visual Audible	Visual Audible	Visual Audible Instant VoiceCall, SMS, WhatsApp alerts
Automatic Reports Via LogTag® Online			✓
Dual Location Monitoring		✓	✓
USB PDF Reports		✓	✓
CDC Compliant	✓	✓	✓
30 Day Alarm History on Display	✓	✓	✓
Recommended Probe*	<a href="#">CP11 Smart Probe</a>	<a href="#">CP10 Smart Probe</a>	<a href="#">CP10 Smart Probe</a>
Price	\$	\$ \$	\$ \$ \$

\*Loggers compatible with additional probes



### Smart Probe Compatible

Make calibration easy, simply unplug your used Smart Probe, then plug in the new one. Done.



### Ultra-Low Temperatures

Wide temperature range, including -90 °C to enable monitoring ultra low temperatures



### Compliance

