LogTag®

Products & Features Matrix

Key:
Sensor:
I = Internal
E = External*
Battery:
F = Fixed
R = Replaceable
Alarm Settings:
P = Preset
C = Configurable

		Main Features			Usage		Memory			Connectivity			Other Features				
		Temperature Measurement Range	Sensor	Battery	Multi-Use	Single-Use	~4,000 Logs Memory	~8,000 Logs Memory	~16,000 Logs Memory	Cradle Required	USB Connector	Wifi Connectivity	Auto PDF Output	Display	Audible Alarm	Alarm Settings	WHO PQS Listed
Temperature Data Loggers	**Product Model**																
Temperature Logger	TRIX-8	-40° to +85° C	I	F	✓			✓		✓						C	✓
High Memory Temperature Logger	TRIX-16	-40° to +85° C	I	F	✓				✓	✓						C	
Temperature Logger with External Probe*	TREX-8	-40° to +99° C	E	F	✓			✓		✓						C	
Single-Use Temperature Logger	SRIC-4	-30° to +60° C	I	F		✓	✓			✓						C	
Logger with 30 day display + Fixed Battery	TRID30-7F	-30° to +60° C	I	F	✓			✓		✓				✓		C	
Logger with 30 day display + Replaceable Battery	TRID30-7R	-30° to +60° C	I	R	✓			✓		✓				✓		C	
WHO PQS listed Logger for vaccines	VaxTag	-30° to +60° C	I	F	✓			✓		✓				✓		P	✓
Logger with 30 day display + External Probe*	TRED30-16R	-40° to +99° C	E	R	✓				✓	✓				✓	✓	C	
USB Temperature Data Loggers																	
Temperature Logger	USRIC-4	-30° to +60° C	I	F		✓	✓				✓					C	
PDF Logger	USRIC-8	-30° to +60° C	I	F		✓		✓			✓		✓			C	
PDF High Memory Logger	UTRIX-16	-30° to +70° C	I	F	✓				✓		✓		✓			C	
PDF Logger with display + Fixed Battery	UTRID-16	-30° to +60° C	I	F	✓				✓		✓		✓	✓		C	✓
PDF Logger with display + Replacaeble Battery	UTRID-16R	-30° to +60° C	I	R	✓				✓		✓		✓	✓		C	
PDF Logger with display & External Probe*	UTRED-16F	-40° to +99° C	E	F	✓				✓		✓		✓	✓		C	
PDF Single-Use Logger with display	USRID-16	-30° to +60° C	I	F		✓			✓		✓		✓	✓		C	
WHO PQS Listed PDF Logger with display	USRID-16W (1 / 2)	-30° to +60° C	I	F		✓			✓		✓		✓	✓		P	✓
Logger with Large display & External Probe*	UTRED30-16	-40° to +99° C	E	R	✓				✓		✓		✓	✓	✓	C	
Wifi Temperature Data Loggers																	
WiFi logger with large display & External Probe*	UTRED30-WIFI	-40° to +99° C	E	R	✓				✓		✓	✓	✓	✓	✓	C	
Low Temp WiFi logger with large display & Ext. Probe*	UTREL30-WIFI	-90° to +40° C	E	R	✓				✓		✓	✓	✓	✓	✓	C	

** Extra Charges Apply For Probes & Accessories*

LogTag®

Products & Features Matrix

Key:
Sensor:
I = Internal
E = External*
Battery:
F = Fixed
R = Replaceable
Alarm Settings:
P = Preset
C = Configurable

		Main Features			Usage		Memory			Connectivity			Other Features				
		Temperature Measurement Range	Sensor	Battery	Multi-Use	Single-Use	~4,000 Logs Memory	~8,000 Logs Memory	~16,000 Logs Memory	Cradle Required	USB Connector	Wifi Connectivity	Auto PDF Output	Display	Audible Alarm	Alarm Settings	WHO PQS Listed
Low-Temperature Data Loggers	**Product Model**																
Low Temp Logger	TRIL-8	-80° to +40° C	I	F	✓			✓		✓						C	
Single-Use Logger	SRIL-8	-80° to +40° C	I	F		✓		✓		✓						C	
Logger with External Probe*	TREL-8	-90° to +40° C	E	F	✓			✓		✓						C	
USB PDF Logger with External Probe*	UTREL-16F	-90° to +40° C	E	F	✓				✓		✓		✓	✓		C	
Logger with 30 day display & External Probe*	TREL30-16	-90° to +40° C	E	R	✓				✓	✓				✓	✓	C	
USB Logger with large display & External Probe*	UTREL30-16	-90° to +40° C	E	R	✓				✓		✓		✓	✓	✓	C	
Temperature and Humidity Data Loggers																	
Humidity & Temperature Logger	HAXO-8	-40° to +85° C	I	F	✓			✓		✓						C	
Single-Use Humidity & Temperature Logger	HASO-8	-40° to +85° C	I	F		✓		✓		✓						C	
USB PDF Humidity/Temperature Logger with display	UHADO-16	-30° to +70° C	I	R	✓				✓		✓		✓	✓	✓	C	
Temperature Indicators																	
Temperature Indicator with 20 day display	TIC20	-30° to +60° C	I	F		✓								✓		P	✓
Temperature Indicator with 4 alarms	TICT	-25° to +60° C	I	F		✓								✓		P	
Freeze Temperature Indicator	TICT iS0°Tag®	-25° to +60° C	I	F		✓								✓		P	✓
Interface Cradles																	
Desktop USB Interface Cradle	LTI-HID	-20° to +60° C	N/A	N/A	✓						✓					N/A	
LTI WiFi Interface Cradle	LTI-WIFI	0° to +40° C	N/A	N/A	✓						✓	✓				N/A	
LTI Wall Mount WiFi Interface Cradle	LTI-WM-WIFI	-25° to +40° C	N/A	N/A	✓						✓	✓				N/A	

** Extra Charges Apply For Probes & Accessories*

LogTag® Online Product Model Features Key

LogTag dataloggers are named using the naming conventions below. Please note that these features may not be accurate, so please to check the product specifications before purchase.

T	Temperature
R	Recording
I	Internal Sensor
X	Extended Temp Range
S	Single Use
C	Commercial Temp Range (-30°C to +60°C)
D	Display
U	USB
E	External Sensor
L	Low Temperature

H	Humidity
F	Fixed Battery
R	Replaceable Battery
W	WHO-PQS Listed
4	~4,000 Log Memory
7	~7,000 Log Memory
8	~8,000 Log Memory
16	~16,000 Log Memory
20	20-Day Display
30	30-Day Display
WIFI	WiFi Enabled

Revision C (020821) © Copyright 2021, LogTag North America Inc. All rights reserved.
LogTag® is a registered trademark of LogTag North America Inc.
LogTag North America Inc. reserves the right to change this specification without notice.

LogTag®